

Known File Filter (KFF)

Installation Guide

Version 7.0.x



AccessData Legal and Contact Information

Document date: November 12, 2018

Legal Information

©2018 AccessData Group, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

AccessData Group, Inc. makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, AccessData Group, Inc. reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, AccessData Group, Inc. makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, AccessData Group, Inc. reserves the right to make changes to any and all parts of AccessData software, at any time, without any obligation to notify any person or entity of such changes.

You may not export or re-export this product in violation of any applicable laws or regulations including, without limitation, U.S. export regulations or the laws of the country in which you reside.

AccessData Group, Inc.
588 West 400 South Suite 350
Lindon, UT 84042
USA

AccessData Trademarks and Copyright Information

The following are either registered trademarks or trademarks of AccessData Group, Inc. All other trademarks are the property of their respective owners.

AccessData®	AD Summation®	Mobile Phone Examiner Plus®
AccessData Certified Examiner® (ACE®)	Discovery Cracker®	MPE+ Velocitor™
AD AccessData™	Distributed Network Attack®	Password Recovery Toolkit®
AD eDiscovery®	DNA®	PRTK®
AD RTK™	Forensic Toolkit® (FTK®)	Registry Viewer®
	LawDrop®	Summation®

A trademark symbol (®, ™, etc.) denotes an AccessData Group, Inc. trademark. With few exceptions, and unless otherwise notated, all third-party product names are spelled and capitalized the same way the owner spells and capitalizes its product name. Third-party trademarks and copyrights are the property of the trademark and copyright holders. AccessData claims no responsibility for the function or performance of third-party products.

Third party acknowledgements:

- AFF® and AFFLIB® Copyright© 2005, 2006, 2007, 2008 Simson L. Garfinkel and Basis Technology Corp. All rights reserved.
Copyright © 2005 - 2009 Ayende Rahien
- FreeBSD ® Copyright 1992-2011. The FreeBSD Project.
- BSD License:
Copyright (c) 2009-2011, Andriy Syrov. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer; Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution; Neither the name of Andriy Syrov nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
- WordNet License:
This license is available as the file LICENSE in any downloaded version of WordNet.
WordNet 3.0 license: (Download)
WordNet Release 3.0 This software and database is being provided to you, the LICENSEE, by Princeton University under the following license. By obtaining, using and/or copying this software and database, you agree that you have read, understood, and will comply with these terms and conditions.: Permission to use, copy, modify and distribute this software and database and its documentation for any purpose and without fee or royalty is hereby granted, provided that you agree with the following copyright notice and statements, including the disclaimer, and that the same appear on ALL copies of the software, database and documentation, including modifications that you make for internal use or for distribution.
WordNet 3.0 Copyright 2006 by Princeton University. All rights reserved. THIS SOFTWARE AND DATABASE IS PROVIDED "AS IS" AND PRINCETON UNIVERSITY MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, PRINCETON UNIVERSITY MAKES NO REPRESENTATIONS OR WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE LICENSED SOFTWARE, DATABASE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS. The name of Princeton University or Princeton may not be used in advertising or publicity pertaining to distribution of the software and/or database. Title to copyright in this software, database and any associated documentation shall at all times remain with Princeton University and LICENSEE agrees to preserve same.
- XMLmind XSL-FO Converter Professional Edition Developer License Agreement:
Distribution
Licensee may not distribute with the Application any component of the Software other than the binary class library (xfc.jar) for the Java™ version and the Dynamic Link Library file (xfc.dll) for the .NET version.
Licensee shall include the following copyright notice: "XMLmind XSL-FO Converter Copyright © 2002-

2009 Pixware SARL", with every copy of the Application. This copyright notice may be placed together with Licensee's own copyright notices, or in any reasonably visible location in the packaging or documentation of the Application.

Licensee may use, distribute, license and sell the Application without additional fees due to Licensor, subject to all the conditions of this License Agreement.

- "Amazon Web Services", "AWS" "AWS Aurora" "AWS Relational Database Service" are trademarks of Amazon.com, Inc. or its affiliates in the United States and/or other countries and is used with permission <https://aws.amazon.com/aispl/trademark-guidelines/>.
- Apache(r), Apache Cassandra and the flame logo is a registered trademark of the Apache Software Foundation in the United States and/or other countries. No endorsement by the Apache Software Foundation is implied by the use of these marks.

Contents

- AccessData Legal and Contact Information 2**
- Contents 5**
- Chapter 1: Getting Started with KFF (Known File Filter) 6**
 - Introducing KFF 6
 - About KFF 8
 - Installing the KFF Server 12
 - Configuring the Location of the KFF Server 18
 - Migrating Legacy KFF Data from Previous Versions 21
 - Importing KFF Data 24
 - Using the KFF Import Utility 26
 - Uninstalling KFF 33
 - Installing KFF Updates 34
 - KFF Library Reference Information 35
 - What has Changed in Version 6.3 and Later 37

Chapter 1

Getting Started with KFF (Known File Filter)

Introducing KFF

This document contains the following information about understanding and getting started using KFF (Known File Filter) with products 6.3 and later. If you are using products version 6.2 and earlier, refer to that version's documentation.

Important: AccessData applications versions 6.3 and later use a new KFF architecture. If you are using one of the following applications version 6.3 or later, you must install and implement the new KFF architecture:

- Forensics products (FTK, FTK Pro, AD Lab, AD Enterprise)
- Summation
- eDiscovery

See [What has Changed in Version 6.3 and Later](#) on page 37.

See [What Changed in Version 7.0](#) on page 39.

The following sections explain how to install and configure the KFF Server and KFF environment.

- [About KFF](#) (page 8)
- [Installing the KFF Server](#) (page 12)
- [Configuring the Location of the KFF Server](#) (page 18)
- [Migrating Legacy KFF Data from Previous Versions](#) (page 21)
- [Importing KFF Data](#) (page 24)
- [Installing KFF Updates](#) (page 34)
- [Uninstalling KFF](#) (page 33)
- [KFF Library Reference Information](#) (page 35)
- [What has Changed in Version 6.3 and Later](#) (page 37)
- [What Changed in FTK and Lab Version 6.4](#) (page 38)
- [What Changed in March of 2018](#) (page 38)

After you have installed and configured the KFF Server and KFF environment refer to the following chapter on how to use KFF.

In the FTK, Lab, and Enterprise User Guides: See [Using the Known File Filter \(KFF\)](#) on page 317.

In the eDiscovery Admin Guide: See [Using KFF \(Known File Filter\)](#) on page 147.

In the Summation Admin Guide: See [Using D-NIST \(Known File Filter\)](#) on page 125.

About the KFF Server and Geolocation

Geolocation (GeoIP) data is used for the Geolocation Visualization feature of several AccessData products.

Important: In versions 6.3 and later, Geolocation data is installed automatically and independently and is no longer tied to KFF.

About KFF

KFF (Known File Filter) is a utility that compares the file hash values of known files against the files in your project. The known files that you compare against may be the following:

- Files that you want to ignore, such as operating system or application files
- Files that you want to be alerted about, such as malware or other contraband files

The hash values of files, such as MD5, are based on the file's content, not on the file name or extension. This helps you identify files even if they are renamed.

Using KFF during your analysis can provide the following benefits:

- Immediately identify and ignore 40-70% of files irrelevant to the project.
- Immediately identify known contraband files.

Introduction to the KFF Architecture

There are two distinct components of the KFF architecture:

- **KFF Server** - The KFF Server is the component that is used to store and process the KFF data against your evidence. After you install the KFF Server, you import your KFF data into it.
See [Installing the KFF Server](#) on page 12.
- **KFF Data** - The KFF data are the hashes of the known files that are compared against the files in your project. The KFF data is organized in KFF Hash Sets and KFF Groups. The KFF data can be comprised of hashes obtained from pre-configured libraries (such as NSRL) or custom hashes that you configure yourself.
See [Components of KFF Data](#) on page 8.

Components of KFF Data

Item	Description
Hash	The unique MD5 or SHA-1 hash value of a file. This is the value that is compared between known files and the files in your project.
Hash Set	A collection of hashes that are related somehow. The hash set has an ID, status, name, vendor, package, and version. In most cases, a set corresponds to a collection of hashes from a single source that have the same status.
Group	KFF Groups are containers that are used for managing the Hash Sets that are used in a project. KFF Groups can contains Hash Sets as well as other groups. Projects can only use a single KFF Group. However, when configuring your project you can select a single KFF Group which can contains nested groups.
Status	The specified status of a hash set of the known files which can be either Ignore or Alert. When a file in a project matches a known file, this is the reported status of the file in the project.

Item	Description
Library	<p>A pre-defined collection of hashes that you can import into the KFF Server. You can use the following pre-defined libraries:</p> <ul style="list-style-type: none"> • NSRL • For law enforcement users, you can also use Project Vic libraries. <p>See About Pre-defined KFF Hash Libraries on page 9.</p>

About the Organization of Hashes, Hash Sets, and KFF Groups

Hashes, such as MD5, SHA-1, etc., are based on the file's content, not on the file name or extension.

You can also import hashes into the KFF Server in **.CSV** format.

For FTK-based products, you can also import hashes into the KFF Server that are contained in **.TSV**, **.HKE**, **.HKE.TXT**, **.HDI**, **.HDB**, **.hash**, **.NSRL**, or **.KFF** file formats.

You can also manually add hashes.

Hashes are organized into Hash Sets. Hash Sets usually include hashes that have a common status, such as Alert or Ignore.

Hash Sets must be organized into to KFF Groups before they can be utilized in a case or project.

About Pre-defined KFF Hash Libraries

There are pre-configured hash sets currently available for KFF that come from federal government agencies and are available in KFF libraries.

See [About KFF Pre-Defined Hash Libraries](#) on page 35.

You can use the following KFF libraries:

- NIST NSRL
See [Importing the NIST NSRL Library](#) on page 29.
- For law enforcement users using forensic products, you can also use Project Vic libraries.
See [Using Project VIC](#) on page 333.

It is not required to use a pre-configured KFF library in order to use KFF. You can configure or import custom hash sets. See your application's *Admin Guide* for more information.

How KFF Works

The Known File Filter (KFF) is a body of MD5 and SHA1 hash values computed from electronic files. Some pre-defined data is gathered and cataloged by several US federal government agencies or you can configure your own. KFF is used to locate files residing within project evidence that have been previously encountered by other investigators or archivists. Identifying previously cataloged (known) files within a project can expedite its investigation.

When evidence is processed with the MD5 Hash (and/or SHA-1 Hash) and KFF options, a hash value for each file item within the evidence is computed, and that newly computed hash value is searched for within the KFF data. Every file item whose hash value is found in the KFF is considered to be a known file.

Note: If two hash sets in the same group have the same MD5 hash value, they must have the same metadata. If you change the metadata of one hash set, all hash sets in the group with the same MD5 hash file will be updated to the same metadata.

The KFF data is organized into Groups and stored in the KFF Server. The KFF Server service performs lookup functions.

Status Values

In order to accelerate an investigation, each known file can be labeled as either Alert or Ignore, meaning that the file is likely to be forensically interesting (Alert) or uninteresting (Ignore). Other files have a status of Unknown.

The Alert/Ignore designation can assist the investigator to hone in on files that are relevant, and avoid spending inordinate time on files that are not relevant. Known files are presented in the Overview Tab's File Status Container, under "KFF Alert files" and "KFF Ignorable."

Hash Sets

The hash values comprising the KFF are organized into hash sets. Each hash set has a name, a status, and a listing of hash values. Consider two examples. The hash set "ZZ00001 Suspected child porn" has a status of Alert and contains 12 hash values. The hash set "BitDefender Total Security 2008 9843" has a status of Ignore and contains 69 hash values. If, during the course of evidence processing, a file item's hash value were found to belong to the "ZZ00001 Suspected child porn" set, then that file item would be presented in the KFF Alert files list. Likewise, if another file item's hash value were found to belong to the "BitDefender Total Security 2008 9843" set, then that file would be presented in the KFF Ignorable list.

In order to determine whether any Alert file is truly relevant to a given project, and whether any Ignore file is truly irrelevant to a project, the investigator must understand the origins of the KFF's hash sets, and the methods used to determine their Alert and Ignore status assignments.

You can install libraries of pre-defined hash sets or you can import custom hash sets. The pre-defined hash sets contain a body of MD5 and SHA1 hash values computed from electronic files that are gathered and cataloged by several US federal government agencies.

See [About KFF Pre-Defined Hash Libraries](#) on page 35.

Higher Level Structure and Usage

Because hash set groups have the properties just described, and because custom hash sets and groups can be defined by the investigator, the KFF mechanism can be leveraged in creative ways. For example, the investigator may define a group of hash sets created from encryption software and another group of hash sets created from child pornography files and then apply only those groups while processing.

About KFF Data Formats

When importing KFF data, you can import the following file formats:

- CSV file format
- Forensics products: .HDB, .HKE, .KFF, .XML, .HASH file formats
- Forensics products used by law enforcement: Project VIC JSON file format

About the CSV Format

When you import or export KFF data, you can import from or export to a CSV format. When you use the .CSV format, you use a single .CSV file at a time. The .CSV file can contain hashes, Hash Sets and KFF Groups that you import or export.

See [Components of KFF Data](#) on page 8.

Using the CSV format	
Exporting to CSV format	<p>When you export KFF data using the CSV format, you can export specific pieces of KFF data, such as one or more Hash Sets or one or more KFF Groups. The exported CSV contains the hashes as well as all of the information about any associated Hash Sets and KFF Groups.</p> <p>Each export is contained in one .CSV file.</p> <p>CSV files can be easily viewed and can be manually edited.</p>
Importing from CSV format	<p>When you import a CSV file, the data in the file is added to your existing KFF data. The CSV file can be a simple file containing only the hashes of files, or it can contain additional information about Hash Sets and KFF Groups.</p> <p>For example, suppose you manually created four Hash Sets and one KFF Group. That would be the only contents in your <i>KFF Server</i>. Suppose you import a .CSV file that contains five hash sets and two KFF Groups. They will be added together for a total of nine Hash Sets and three KFF Groups.</p> <p>To import .CSV files, you can do either of the following:</p> <ul style="list-style-type: none">• Use the KFF Import feature in your application. See <i>Using the Known File Feature</i> chapter.• Use the stand-alone KFF Import Utility. See Importing KFF Data on page 24.

To view a sample of a .CSV file that contains binaries and Hash Sets and KFF Groups, perform a CSV export and view the file in Excel. You can also use the format of CSV files that were exported in previous versions.

Installing the KFF Server

About Installing the KFF Server

In order to use KFF, you must first install and configure a KFF Server.

- For product versions 6.3 and later, you install a KFF Server by installing Apache Cassandra.
- For product versions 5.6 - 6.2, you install a KFF Server by installing the AccessData Elasticsearch.

Where you install the KFF Server depends on the product you are using with KFF.

See [Determining Where to Install the KFF Server](#) on page 14.

About KFF Server Versions

The KFF Server (AccessData Elasticsearch Windows Service) may be updated from time to time. It is best to use the latest version.

Product Version	KFF Server	Released	Installation Instructions
6.3, 6.4, 6.5, 7.0	Apache Cassandra Version 3.11.2	<ul style="list-style-type: none">• March 2018 (stand-alone update)	<p>See Determining Where to Install the KFF Server on page 14.</p> <p>See Downloading the Latest KFF Installation Files on page 13.</p> <p>This 3.11.2 version should be installed over the 3.11.0 version (do not uninstall 3.11.0). This will maintain your KFF data.</p>
6.3	Apache Cassandra Version 3.11.0	<ul style="list-style-type: none">• October 2017 with 6.3 versions of<ul style="list-style-type: none">■ FTK-based products■ Summation■ eDiscovery	<p>Note: This version is not compatible with the Java version 8 update 161. This was fixed with Cassandra database 3.11.2</p>

About Upgrading from Earlier Versions

If you have used KFF with applications with a previous KFF Server architecture (products 6.2 and earlier), you can migrate your legacy KFF data to the new architecture.

See [Migrating Legacy KFF Data from Previous Versions](#) on page 21.

Process for Installing KFF

The process for installing KFF is as follows:

1. [Downloading the Latest KFF Installation Files](#) (page 13)
2. [Determining Where to Install the KFF Server](#) (page 14)
3. [Installing the KFF Server](#) (page 16)
4. Configuring the KFF Server location:
 - [Configuring the KFF Server Location on AD Lab and AD Enterprise](#) (page 18)
 - [Configuring the KFF Server Location on Summation or eDiscovery](#) (page 19)
5. (Optional) Upgrading or importing KFF data.
 - See [Migrating Legacy KFF Data from versions 5.5 and earlier](#) on page 22.
 - [About Importing KFF Data](#) (page 24)
 - [Importing Pre-defined KFF Data Libraries](#) (page 28)

Downloading the Latest KFF Installation Files

You can download ISO files which has the latest KFF files. Files may be updated from time to time.

To download the latest KFF Installation Files

1. Go to the AccessData [Current Releases - Digital Forensics](#) product download page.
You can also download the file from the FTK or AD Lab product download pages.
2. Expand the following:
 - **Known File Filter (KFF) Compatible with 5.6 and up**
3. Click the following:
 - **DOWNLOAD Page** for *Known File Filter (KFF) Compatible with 6.4 and Newer Versions*.
4. Click **Download Now**.

Determining Where to Install the KFF Server

Where you install the KFF Server depends on the application and environment you are running.

- For FTK and FTK Pro applications, the KFF Server **must** be installed on the same computer that runs the FTK Examiner application.
- For AD Lab and AD Enterprise, applications, the KFF Server can be installed on the same computer that runs the FTK Examiner application or on a different computer. For performance purposes, it is generally installed on a different computer.
See [AD Lab and AD Enterprise](#) on page 14.
- For Summation or eDiscovery, the KFF Server may be installed on either the same computer as the application or on a different computer. For large environments, it is recommended that the KFF Server be installed on a dedicated computer.
See [Summation or eDiscovery](#) on page 15.
- After installing the KFF Server, you configure the application with the location of the KFF Server.

See [Configuring the Location of the KFF Server](#) on page 18.

AD Lab and AD Enterprise

With AD Lab and Enterprise, you generally install the KFF Server on a different computer than the application.

Special Configuration Steps for KFF

When you install the KFF Server on a different computer than the application you perform special configuration steps by doing the following:

- Configure the KFF Server location.
See [Configuring the KFF Server Location on AD Lab and AD Enterprise](#) on page 18.
- Application version 6.3 and later:
 - During the installation of Cassandra, you must enable and configure Remote Access.
See [Installing the KFF Server](#) on page 16.
 - If you installed Cassandra without enabling remote access, you can manually configure Cassandra.
See [Manually Configuring Remote Setting for Cassandra](#) on page 20.

Summation or eDiscovery

With Summation or eDiscovery, you may have one of the following environments. The type of environment determines where and how to configure the KFF Server.

Environment	KFF Server Location and Configuration
Single Server	<p>All components of the application are installed on a single server.</p> <ul style="list-style-type: none">• You can install the KFF Server on this server or a different remote computer.• If you install the KFF Server on the same server, no special configuration for KFF is needed.• If you install the KFF Server on a remote computer, you must perform special configuration steps for KFF.
Distributed Components with Local Processing	<p>Components of the application are installed on multiple servers. For example, the MAP component is on one server and other application components, such as WCF Services and Local Processing are installed on a separate computer.</p> <ul style="list-style-type: none">• You can install the KFF Server on the same server as WCF Services and Local Processing or on a different remote computer.• If you install the KFF Server on the same server, no special configuration for KFF is needed.• If you install the KFF Server on a remote computer, you must perform special configuration steps for KFF.
Distributed Processing Manager and Engines	<p>You have installed the Distributed Processing Manager and Distributed Processing Engines.</p> <ul style="list-style-type: none">• You can install the KFF Server on any computer.• You must perform special configuration steps for KFF.
Dedicated KFF Server	<p>For performance, you can install the KFF Server on a dedicated computer.</p> <ul style="list-style-type: none">• You must perform special configuration steps for KFF.

If you do not need to perform special configuration steps, you can use default settings.

Special Configuration Steps for KFF

If needed, when you perform special configuration steps, you must do the following:

- Configure the KFF Server location by editing two application configuration files.
See [Configuring the KFF Server Location on Summation or eDiscovery](#) on page 19.
- Application version 6.3 and later:
 - During the installation of Cassandra, you must enable and configure remote access.
See [Installing the KFF Server](#) on page 16.
 - If you installed Cassandra without enabling remote access, you can manually configure Cassandra.
See [Manually Configuring Remote Setting for Cassandra](#) on page 20.

Installing the KFF Server

How you install the KFF Server depends on version of the product you are running.

For product versions 6.3 and later, you install the KFF Server by installing Apache Cassandra 3.11.2.

Cassandra Prerequisites

Python 2.7	When you install Cassandra, it will also automatically install Python 2.7.13 if needed.
Java 8 (64-bit)	<p>Important: In order to install Cassandra, you must have 64-bit Java for Windows version 8. No other version of Java (7 or 9) is currently supported. The latest version of Java that has been tested with KFF is Java 8 update 192 (64-bit).</p> <p>Before installing Cassandra, you must install Java 8.</p> <p>To install Java 8, go to:</p> <p>https://java.com/en/download/windows-64bit.jsp</p> <p>If you are using a 32-bit browser, your browser may automatically download the 32-bit version. You must use the 64-bit version.</p> <p>Important: A previous release of the Cassandra database (3.11.0) that was released with 6.3 is not compatible with the Java version 8 update 161 or higher. If using Cassandra database 3.11.0, update to 3.11.2. See About KFF Server Versions on page 12.</p>

Cassandra and Firewalls

During the installation, if you check the box to *Enable Remote Access*, the installer creates an inbound exception rule for the port entered in the Cassandra installer (if the rule has not already been created).

The rule has the following attributes:

- name = AccessData Cassandra Remote Access Port
- direction = in
- program = "<install directory>\Cassandra\bin\daemon\prunsv.exe"
- local port = 9042 (or whatever the user entered)
- protocol = tcp

If you uninstall Cassandra, the installer checks to see if Enable Remote Access was checked during install, and if it was, the installer looks for the above firewall rule using the 5 listed attributes, and if it finds the rule, it removes it from the firewall.

Installing Cassandra

To install Cassandra

1. Select the computer that you want to install Cassandra on.
See [Determining Where to Install the KFF Server](#) on page 14.
2. If needed, install 64-bit Java 8.
See [Cassandra Prerequisites](#) on page 16.
3. Use one of the following to access `AccessData_Cassandra_Installer.exe`:
 - Installation Disk
 - Download ISO
See [Downloading the Latest KFF Installation Files](#) on page 13.
4. Launch `Cassandra\AccessData_Cassandra_Installer.exe`.
5. If needed, click **Install** to install Python 2.7 (x64).
6. On the Cassandra installer *Welcome* page, click **Next**.
7. Accept the license terms and click **Next**.
8. Verify or change the the *Destination Folder* and click **Next**.
9. If needed, configure Remote Access.
See [Determining Where to Install the KFF Server](#) on page 14.

Important: If installing for FTK, do not enable Remote Access. FTK requires a setting of localhost.

- 9a. Select *Enable Remote Access*.
- 9b. In the *RPC_Address* field, enter the IP address of the computer you are installing on.
For example, 10.10.10.10.
- 9c. In the *Native Transport Port Number* field, leave the default 9042.
- 9d. Click **Next**.
If you do not enable Remote Access during installation, you can manually configure it later.
See [Manually Configuring Remote Setting for Cassandra](#) on page 20.
10. If you enabled Remote Access, set the User Credentials for the service and click **Next**.
11. Click **Install** to perform the installation.
12. Click **Finish**.
13. If your `AccessData` application is already open, restart it.

Configuring the Location of the KFF Server

After installing the KFF Server, on the computer running the application, such as Summation, eDiscovery, FTK, or AD Lab, you configure the location of the KFF Server.

Do one of the following:

- [Configuring the KFF Server Location on AD Lab and AD Enterprise](#) (page 18)
- [Configuring the KFF Server Location on Summation or eDiscovery](#) (page 19)
- [Manually Configuring Remote Setting for Cassandra](#) (page 20)

Configuring the KFF Server Location on AD Lab and AD Enterprise

If running FTK, you use default settings.

If running with AD Lab or AD Enterprise, and if not using default settings, before using KFF, you must configure the location of the KFF Server.

Important: To configure KFF, you must be logged in with Admin privileges.

To view or edit KFF configuration settings

1. In the *Case Manager*, click **Tools > Preferences > Configure KFF**.
2. You can set or view the address of the KFF Server.
 - If you installed the KFF Server on the same computer as the application, this value will be localhost.
 - If you installed the KFF Server on a different computer, identify the KFF server.
3. Click **Test** to validate communication with the KFF Server.
4. Click **Save**.
5. Click **OK**.

Configuring the KFF Server Location on Summation or eDiscovery

When using the KFF Server with Summation or eDiscovery, two configuration files must point to the KFF Server location.

Important: If you are upgrading to 6.3 or later from 6.2 or earlier, the syntax of and the port values for the KFF Server have changed. If the KFF Server is not being recognized, make sure that the two config files are correct.

See [What has Changed in Version 6.3 and Later](#) on page 37.

KFF Server Location scenarios

If one of the following is true, you can use the default settings and the KFF Server location is configured as "localhost".

- Your Summation or eDiscovery installation is on a single server
- Your Summation or eDiscovery installation is on multiple servers, and you install the KFF Server on the same server that is running WorkManager

If needed, you can verify the settings without changing them.

If one of the following is true, you must manually specify the location of the KFF Server:

- If you change the location of your KFF Server
- If you install the KFF Server on a different computer than is running WorkManager
- If you are using distributed processing

For KFF processing to work correctly in this situation, change the the `KFFServerURL` setting from "localhost" to the actual IP address.

Manually Verifying or Configuring the KFF Server Location on products 6.3 and later

1. Configure `AdgWindowsServiceHost.exe.config`:
 - 1a. On the computer running the work manger service, go to `C:\Program Files\AccessData\Common\FTK Business Services`.
 - 1b. Open `AdgWindowsServiceHost.exe.config`.
 - 1c. Find the line `<add key="KFFServerUrl" value="localhost:9042" />`.
Note: 9042 is the default port for Cassandra.
 - 1d. If needed, change `localhost` to be the location IP address of your KFF server.
For example, `value="10.10.10.10:9042"`
Otherwise, leave as `localhost`.
 - 1e. Leave the following line unchanged:
`<add key="KFFServerDBType" value="Cassandra" />`
 - 1f. Save and close the file.
 - 1g. If you changed the file, restart the `AccessData Business Services Common` service.

2. Configure `Infrastructure.WorkExecutionServices.Host.exe.config`:
 - 2a. On the computer running the work manger service, go to `C:\Program Files\AccessData\Discovery\WorkManager`.
 - 2b. Open `Infrastructure.WorkExecutionServices.Host.exe.config`.
 - 2c. Find the line `<add key="KFFServerUrl" value="localhost:9042" />`.
Note: 9042 is the default port for Cassandra.
 - 2d. If needed, change `localhost` to be the location IP address of your KFF server.
For example, `value="10.10.10.10:9042"`
Otherwise, leave as `localhost`.
 - 2e. Leave the following line unchanged:
`<add key="KFFServerDBType" value="Cassandra" />`
 - 2f. Save and close the file.
 - 2g. If you changed the file, restart the *AccessData Work Manager* service.
3. Migrate or Import your KFF Hash Data.
See [About Importing KFF Data](#) on page 24.

Manually Configuring Remote Setting for Cassandra

In some situations Cassandra needs be to configured to enable Remote Access.

See [Determining Where to Install the KFF Server](#) on page 14.

During the installation of Cassandra there is the option to *Enable Remote Access* and then set the `RPC_Address` (the IP address of the computer that Cassandra is installed on).

If you set these settings correctly during the installation, no further configuration is needed.

However, if you did not enable remote access or make a change, you can manually configure the remote settings for Cassandra.

Note: Use an editor that supports YAML files.

To manually configuring remote settings for Cassandra

1. Go to the location that you installed Cassandra.
By default, it is `C:\Program Files\AccessData\Cassandra`.
2. Open the `\conf` folder.
3. Edit the `cassandra.yaml` file.
4. Search for `rpc_address`:
5. Change the address from local host to the IP or DNS name of the computer running Cassandra.
For example change `rpc_address: localhost` to `rpc_address: 10.10.10.10`
6. Search for `native_transport_port`:
7. Verify that the setting is:
`native_transport_port: 9042` (or the port you are using)
8. Save and exit the file.
9. Restart the *AccessData Cassandra* service.

Migrating Legacy KFF Data from Previous Versions

You can migrate KFF Data from a previous KFF Server architecture to a newer one.

- See [Migrating Legacy KFF Data from versions 5.6 - 6.2 to 6.4](#) on page 21.
- See [Migrating Legacy KFF Data from versions 5.5 and earlier](#) on page 22.

Migrating Legacy KFF Data from versions 5.6 - 6.2 to 6.4

If you have are using applications version 6.3 and later and you previously used KFF with applications versions 5.5 - 6.2, you can migrate the older data from the Elasticsearch KFF Server to the new KFF Server architecture used in 6.3 and later. To migrate the KFF data, you use the *AccessData Has Manager Migration Tool*. This tool is a separate Windows-based application.

Important: Please note the following:

- Applications version 6.3 and later can only use the new KFF architecture that was introduced in versions 6.3. If you want to use KFF data from previous versions, you must migrate the data.
- If you have NSRL, NDIC, or DHS data in your legacy data, those sets will not be migrated. You must re-import them using the 6.3 versions or later of those libraries. Only legacy custom KFF data will be migrated.
- You must use the same version of the KFF Migration as the product you are using. If you are using 6.4, you must use the 6.4 version of the KFF Migration Tool.
- You cannot migrate data from 5.5 and earlier directly to 6.3 or later. You must do a two-step migration process and migrate first to the 5.6-6.2 format.
- If you already have data in Cassandra and you migrate from Elasticsearch, if the same hash exists on both servers, and one if either one of them has an Alert status, it will be given an Alert status. Otherwise, data will be migrated with the same values.

Legacy KFF data is migrated to KFF Groups and Hash Sets on the new KFF Server.

You migrate data using the KFF Migration Tool. To use the KFF Migration Tool, you identify the following:

- The server where the legacy Elasticsearch KFF data is located.
- The server where the legacy Elasticsearch KFF data will be located to (the Cassandra location).

To install the KFF Migration Tool

1. You can install the KFF Migration Tool onto any computer as long as it can access the servers running Elasticsearch and Cassandra.
2. Use one of the following to access the KFF_Migration_Tool.exe installer:
 - Installation Disk:
Run the autorun.exe
Click the **Hash Manager Migration Tool**.
 - Download ISO:
See [Downloading the Latest KFF Installation Files](#) on page 13.
Run KFF_Migration\KFF_Migration_Tool.exe
3. Complete the installation wizard.
The default path is Program Files (x86)\AccessData\HashManagerMigration.
You can use the default or enter a new path.
4. The tool is automatically opened after installation.

To migrate legacy KFF data

1. Launch the KFF Hash Manager Migration Tool.
2. Enter the location and port of the legacy Elasticsearch KFF data.
For example, if Elasticsearch is on the same computer, you can use the default location of `http://localhost:9200`.
If it is on a different computer, enter the IP address and port of the computer. For example, `http://10.10.10.10:9200`.
3. Enter the location of the new KFF server (Cassandra database).
For example, if Cassandra is on the same computer, you can use the default location of `localhost`. If it is on a different computer, enter the IP address, for example, `10.10.10.10`.
4. Click **Start Migration**.

Migrating Legacy KFF Data from versions 5.5 and earlier

If you have used KFF with applications versions 5.5 and earlier, you can migrate that data from the legacy KFF Server to the Elasticsearch KFF Server architecture that was used in version 5.6 - 6.2. You cannot migrate data from 5.5 directly to 6.3 or later. Instead, you must upgrade the legacy to a 5.6 - 6.2 format, then migrate that to 6.3.

Important: Applications version 5.6 - 6.2 can only use the Elasticsearch KFF architecture. If you want to use KFF data from previous versions, you must migrate the data.

Important: If you have NSRL, NDIC, or DHS data in your legacy data, those sets will not be migrated. You must re-import them using the 5.6 - 6.2 versions of those libraries. Only legacy custom KFF data will be migrated.

Legacy KFF data is migrated to KFF Groups and Hash Sets on the new KFF Server.

Because KFF Templates are no longer used, they will be migrated as KFF Groups, and the groups that were under the template will be added as sub-groups.

You migrate data using the KFF Migration Tool. To use the KFF Migration Tool, you identify the following:

- The Storage Directory folder where the legacy KFF data is located.
This was folder was configured using the KFF Server Configuration utility when you installed the legacy KFF Server. If needed, you can use this utility to view the KFF Storage Directory. The default location of the `KFF_Config.exe` file is `Program Files\AccessData\KFF`.
- The URL of the new KFF Server (the computer running the AccessData Elastic Search Windows Service)
This is populated automatically if the new KFF Server has been installed.

To install the KFF Migration Tool

1. On the computer where you have installed the KFF Server, access the KFF Installation disc, and run the `autorun.exe`.
2. Click the *64 bit* or *32 bit* **Install KFF Migration Utility**.
3. Complete the installation wizard.

To migrate legacy KFF data

1. On the legacy KFF Server, you must stop the KFF Service.
You can stop the service manually or use the legacy `KFF Config.exe` utility.
2. On the new KFF Server, launch the KFF Migration Tool.
3. Enter the directory of the legacy KFF data.

4. The URL of Elasticsearch should be listed.
5. Click **Start**.
6. When completed, review the summary data.

Importing KFF Data

About Importing KFF Data

You can import hashes and KFF Groups that have been previously configured.

You can import KFF data in one of the following formats:

KFF Data sources that you can import

Source	Description
Pre-configured KFF libraries	<p>You can import KFF data from the following pre-configured libraries</p> <ul style="list-style-type: none">• NIST NSRL• Law enforcement users: Project VIC <p>To import large KFF libraries, use the KFF Import Utility. See About KFF Data Import Tools on page 24. See Importing Pre-defined KFF Data Libraries on page 28. See KFF Library Reference Information on page 35.</p>
Custom Hash Sets and KFF Groups	<p>You can import custom hashes from CSV and other file types. See About the CSV Format on page 11.</p> <p>You can import custom CSV files either through the application or the KFF Import Utility.</p> <p>Other file types can be imported in FTK. See About KFF Data Import Tools on page 24.</p>

About KFF Data Import Tools

When you import KFF data, you can use one of two tools:

KFF Data Import Tools

The application's Import feature	<p>The KFF management feature in the application lets you import .CSV files (especially files that only have one KFF status).</p> <p>For FTK-based forensics products, you can also import custom hashes from the following file types:</p> <ul style="list-style-type: none">• Delimited files (CSV or TSV)• Hash Database files (HDB)• FTK Exported KFF files (KFF)• FTK Supported XML files (XML)• FTK Exported Hash files (HASH)• Project VIC JSON files <p>To import these kinds of files, use the KFF Import feature in your application. See <i>Using the Known File Feature</i> chapter. You can also manually create your own KFF hash set data.</p>
----------------------------------	--

KFF Data Import Tools

KFF Import Utility

You can import files using the KFF Import Utility.

It is recommended that you use the KFF Import Utility to import files in the following situations:

- A CSV file that has a mixture of Alert and Ignore statuses.
- Large pre-configured libraries:
 - NIST NSRL

See [Using the KFF Import Utility](#) on page 26.

Important: You must use the same version of the KFF Import Utility as the product you are using. If you are using 6.4, you must use the 6.4 version of the KFF Import Utility to import the NSRL library into the KFF Server.

About Default Status Values

When you import KFF data, you configure a default status value of Alert or Ignore. When adding Hash Sets to KFF Groups, you can configure the KFF Groups to use the default status values of the Hash Set or you can configure the KFF Group with a status that will override the default Hash Set values.

See [Components of KFF Data](#) on page 8.

About Duplicate Hashes

If multiple Hash Set files containing the same Hash identifier are imported into a single KFF Group, the group keeps the last Hash Set's metadata information, overwriting the previous Hash Sets' metadata. This only happens within an individual group and not across multiple groups.

Using the KFF Import Utility

It is important that you use the correct version of the KFF Import Utility with the version of the application you are using. The KFF Import Utility was modified significantly for 6.3.

Important: You must use the same version of the KFF Import Utility as the product you are using.

- If you are using 6.4, you must use the 6.4 version of the KFF Import Utility to import the NSRL library into the KFF Server.
- If you are using 6.3, you must use the 6.3 version of the KFF Import Utility to import the NSRL library into the KFF Server.

Using the KFF Import Utility versions 6.3 and later

About the KFF Import Utility

Due to the large size of some KFF data, a stand-alone KFF Import utility is available to use to import the data. This KFF Import utility can import large amounts of data faster than using the import feature in the application. It is recommended that you install and use the KFF Import utility to import the following pre-configured libraries:

- NIST NSRL

After importing NSRL libraries, these libraries are displayed in the *Currently Installed Sets* list.

See [Components of KFF Data](#) on page 8.

You can also use the KFF Import Utility to remove the NSRL, NDIC, or DHS indexes that you have imported.

Installing the KFF Import Utility versions 6.3, 6.4, and later

You must use the matching version of the KFF Import Utility with your application, for example, 6.3 or 6.4.

To install the KFF Import Utility

1. On the computer where you have installed the KFF Server, access the KFF Installation disc, and run the `autorun.exe`.
2. Use one of the following to access the `KFF_Import_Utility.exe` installer:
 - Installation Disk:
Run the `autorun.exe`
Click the **Install KFF Import Utility**.
 - Download ISO:
See [Downloading the Latest KFF Installation Files](#) on page 13.
Run `KFFImportUtil\KFF_Migration_Tool.exe`
3. Complete the installation wizard.
4. To import libraries, see [About Importing Pre-defined KFF Data Libraries](#) on page 28.

Importing a CSV Using the KFF Import Utility versions 6.3 and later

You can import Hash Sets and KFF Groups by importing a custom CSV file.

See [About the CSV Format](#) on page 11.

To import a CSV using the KFF Import Utility

1. Open the KFF Import Utility.
2. Click the *Browse ..* button and locate the CSV that you want to import.
3. Click **Open**.
4. (Optional) - Enter package, vendor, version, etc.
5. If you installed Cassandra enabling Remote Access, in the *Server address* field, you must enter the computer's IP that has Cassandra installed on it, even if it is on the same computer as the import utility. Otherwise, leave it as localhost.
6. Click **Import**.
7. When complete, click **OK**.

Verifying a File Using the KFF Import Utility versions 6.3 and later

You can verify imported Hash Sets and KFF Groups to ensure the correct file is being imported.

To verify a file using the KFF Import Utility

1. Open the KFF Import Utility.
2. Click the *Browse ..* button and locate the file that you want to import.
3. (Optional) - Enter set name, package, vendor, version, and set status.
4. If you installed Cassandra enabling Remote Access, in the *Server address* field, you must enter the computer's IP that has Cassandra installed on it, even if it is on the same computer as the import utility. Otherwise, leave it as localhost.
5. Click **Verify**.
6. When complete, the Success window will appear, showing the following details:
Group Count, Set Count, Hash Count, Photo DNA Count
7. If you would like to open the log for further examination of the data, select **Yes**. If not, select **No** and the window will close.

Removing Pre-defined KFF Libraries Using the KFF Import Utility version 6.3 and later

You can remove a pre-defined KFF Library that you have previously imported.

You cannot see or remove existing custom KFF data (your own CSVs or manually entered data).

To remove pre-defined KFF Libraries

1. On the KFF Server, open the KFF Import Utility.
2. Select the library that you want to remove.
3. Click **Remove**.

Importing Pre-defined KFF Data Libraries

About Importing Pre-defined KFF Data Libraries

After you install the KFF Server, you can import pre-defined NIST NSRL libraries.

See [About KFF Pre-Defined Hash Libraries](#) on page 35.

Important: In versions 6.3, you must import specific files for these versions. It is recommend that you use the KFF Import Utility.

After importing pre-defined KFF Libraries, you can remove them from the KFF Server.

- [Removing Pre-defined KFF Libraries Using the KFF Import Utility version 6.3 and later](#) (page 27)

See the following sections:

- [Importing the NIST NSRL Library](#) (page 29)

Importing the NIST NSRL Library

To import NSRL data in applications version 6.3, 6.4, 7.0, and later, you can do one of the following:

- Download version 2.58 or later RDS files from nist.gov and import them.
See [Downloading and Importing the NIST NSRL Files from NIST.ORG](#) on page 29.
- Download version 2.54 files from AccessData and import them.
See [Downloading and Importing the NIST NSRL Files from NIST.ORG](#) on page 29.

Important: The NSRL library is very large. It can take several hours to import it.

Downloading and Importing the NIST NSRL Files from NIST.ORG

You can download the latest ISO files directly from the NIST.GOV.

After you have downloaded the files, you import them into the KFF Server.

Before importing NSRL data, we recommend that you verify the hashes of the iso files that you downloaded from NIST. This assures that the data has not been corrupted.

Important: Please note the following:

- The complete NSRL library data is contained in a large (3 GB) .ZIP file in the image file. When expanded, the data is about 14 GB.
- You must not have a previous version version of the NSRL library installed. If needed, uninstall the previous version first.

To download NSRL files from NIST.ORG

1. Go to <https://www.nist.gov/software-quality-group/national-software-reference-library-nsrl>
2. Click **NSRL Download**.
3. Click **Current RDS Hash Sets**.
4. Click and download **Modern RDS**.
5. Compare and the hashes of your downloaded iso files with the hashes listed at:
<https://s3.amazonaws.com/rds.nsl.nist.gov/RDS/current/version.txt>
(This address is case-sensitive)

To prepare NSRL files for importing

1. Mount the RDS ISO file.
2. Create a folder that you can browse to from the Import Utility (for example, `RDS_258_modern`).
3. Extract the `NSRLFile.txt.zip` file into that RDS folder.
4. Copy the following files from the ISO image to that same RDS folder:
 - `NSRLProd.txt`
 - `NSRLOS.txt`
 - `NSRLMfg.txt`
5. Create an `AppTypes.txt` file.

In this file, you can specify application files that you may want to flag as Alert rather than Ignore.

 - 5a. In the same folder as the `NSRLFile.txt.zip` file, create a text file named `AppTypes.txt`.
 - 5b. In the file, include the following text:

This is a text file listing the application types (one per line) which should have "Alert" status set:

Anti-KeyLogger
Computer Investigation
Data Encryption
Disk Wiper
Encryption
Forensic
Forensic Toolkit
Hacker Tool
Keyboard Logger
Steganography
 - 5c. Save and exit the file.
6. Verify that the folder has the following files:
 - `NSRLProd.txt`
 - `NSRLOS.txt`
 - `NSRLMfg.txt`
 - `NSRLFile.txt`
 - `AppTypes.txt`

To import the NIST NSRL library (2.58 or later)

1. On the KFF Server, launch the 6.3 or later version of the *KFF Import Utility*.
See [About Importing KFF Data](#) on page 24.
2. Do the following:
 - 2a. In the *File to Import* field, browse to and select the `NSRLFile.txt` file that you previously extracted.
 - 2b. If you installed Cassandra enabling Remote Access, in the *Server address* field, you must enter the computer's IP that has Cassandra installed on it, even if it is on the same computer as the import utility. Otherwise, use `localhost`.
 - 2c. Click **Import**.
 - 2d. When the import is complete, click **OK**.
 - 2e. The NSRL library will be listed in the *Currently Installed Sets*.

Importing the NIST NSRL Library Files from AccessData (v2.54)

You can download version 2.54 files from AccessData and import them.

See [About NSRL Library Files Provided by AccessData](#) on page 31.

Important: The NSRL library data is contained in a large (3.75 GB) .ZIP file. When expanded, the data is about 21.7 GB. Make sure that your file system can support files of this size.

About NSRL Library Files Provided by AccessData

You can import the NSRL library into your KFF Server. During the import, two KFF Groups are created: NSRL_Alert and NSRL_Ignore. In FTK-based products, these two groups are automatically added to the Default KFF Group.

The NSRL libraries are updated from time to time. The NSRL import feature supports appending new data and updating existing data when importing a newer version. To import and maintain the NSRL data, you do the following:

Process for Importing and Maintaining the NIST NSRL Library

1. Import the complete NSRL library.	You must first install the most current complete NSRL library. You can later add updates to it. To access and import the complete NSRL library, see Importing the NIST NSRL Library (page 29)
2. Import updates to the library	When updates are made available, import the updates to bring the data up-to-date. See Installing KFF Updates on page 34. Important: In order to use the NSRL updates, you must first import the complete library. When you install an NSRL update, you must keep the previous NSRL versions installed in order to maintain the complete set of NSRL data.

Available NRSL library files (new format)

NSRL Library Release	Released	Information
Complete library version 2.54 (source .ZIP file)	Mar 2017	For use only with applications version 5.6 and later. Contains the full NSRL library up through update 2.54.
Complete library version 2.45 (source .ZIP file)	Nov 2014	For use only with applications version 5.6 and later. Contains the full NSRL library up through update 2.45.

To install the v 2.54 NSRL library

1. On the computer that you want to be the KFF Server, extract the nsrlsource_2.54.zip file that is at the root of the ISO.
2. On the computer that you want to be the KFF Server, install the AccessData Cassandra Service.
3. Install the *KFF Import Utility* version 6.3.
4. Use the *KFF Import Utility* to import the NSRL library by doing the following:

- 4a. Launch the *KFF Import Utility*.
- 4b. Browse to the NSRLFile.txt that is contained in the nsrsource_2.54 folder.
- 4c. Click **Open**.
- 4d. Click **Import**.
- 4e. When the import is complete, a finished window pops up, click OK.

Uninstalling KFF

You can uninstall KFF application components independently of the KFF Data.

Main version	Description
Applications 5.6 to 6.2	<p>For applications version 5.6 and later, you uninstall the following components:</p> <ul style="list-style-type: none">• <i>AccessData Elasticsearch Windows Service</i> (KFF Server) v1.2.7 and later Note: Elasticsearch is used by multiple features in various applications, use caution when uninstalling this service or the related data.• <i>AccessData KFF Import Utility</i> (v5.6 and later)• <i>AccessData KFF Migration Tool</i> (v1.0 and later)• <i>AccessData Geo Location Data</i> (v2014.10 and later) Note: This component is not used by the KFF feature, but with the KFF Server for the geolocation visualization feature. <p>The location of the KFF data is configured when the <i>AccessData Elasticsearch Windows Service</i> was installed. By default, it is located at C:\Program Files\AccessData\Elasticsearch\Data.</p>
Applications 5.5 and earlier	<p>For applications version 5.5 and earlier, you can uninstall the following components:</p> <ul style="list-style-type: none">• KFF Server (v1.2.7 and earlier) Note: The KFF Server is also used by the geolocation visualization feature.• <i>AccessData Geo Location Data</i> (1.0.1 and earlier) This component is not used by the KFF feature, but with the KFF Server for the geolocation visualization feature. <p>The location of the KFF data was configured when the <i>KFF Server</i> was installed. You can view the location of the data by running the <i>KFF.Config.exe</i> on the KFF Server.</p> <p>If you are upgrading from 5.5 to 5.6, you can migrate your KFF data before uninstalling the KFF Server.</p>

Installing KFF Updates

From time to time, AccessData will release updates to the KFF Server and the KFF data libraries.

Some of the KFF data updates may require you to update the version of the KFF Server.

To check for updates, do the following:

1. Go to the KFF product download page.
See [Downloading the Latest KFF Installation Files](#) on page 13.
2. Check for updates.
 - See [About KFF Server Versions](#) on page 12.
 - See [Importing the NIST NSRL Library](#) on page 29.
3. If there are updates, download them.
4. Install or import the updates.

KFF Library Reference Information

About KFF Pre-Defined Hash Libraries

This section includes a description of pre-defined hash collections that can be added as AccessData KFF data. The following pre-defined libraries are currently available for KFF and come from federal government agencies:

- NIST NSRL (The default library installed with KFF)

For law enforcement users, you can also use Project Vic libraries.

See [Using Project VIC](#) on page 333.

Use the following information to help identify the origin of any hash set within the KFF

- The NSRL hash sets do not begin with “ZZN” or “ZN”. In addition, in the AD Lab KFF, all the NSRL hash set names are appended (post-fixed) with multi-digit numeric identifier. For example: “Password Manager & Form Filler 9722.”

Once an investigator has identified the vendor from which a hash set has come, he/she may need to consider the vendor’s philosophy on collecting and categorizing hash sets, and the methods used by the vendor to gather hash values into sets, in order to determine the relevance of Alert (and Ignore) hits to his/her project. The following descriptions may be useful in assessing hits.

NIST NSRL

The NIST NSRL collection is described at: <http://www.nsrl.nist.gov/index.html>. It is composed entirely of hash sets being generated from application software. So, all of its hash sets are given Ignore status by AccessData staff except for those whose names make them sound as though they could be used for illicit purposes.

The NSRL collection divides itself into many sub-collections of hash sets with similar names. In addition, many of these hash sets are “empty”, that is, they are not accompanied by any hash values. The size of the NSRL collection, combined with the similarity in set naming and the problem of empty sets, allows AccessData to modify (or selectively alter) NSRL’s own set names to remove ambiguity and redundancy.

Find contact info at <http://www.nsrl.nist.gov/Contacts.htm>.

Higher Level KFF Structure and Usage

Since hash set groups have the properties just described (and because custom hash sets and groups can be defined by the investigator) the KFF mechanism can be leveraged in creative ways. For example:

- You could define a group of hash sets created from encryption software and another group of hash sets created from child pornography files. Then, you would apply only those groups while processing.
- You could also use the Ignore status. You are about to process a hard drive image, but your search warrant does not allow inspection of certain files within the image that have been previously identified. You could do the following and still observe the warrant:
 - 4a. Open the image in Imager, navigate to each of the prohibited files, and cause an MD5 hash value to be computed for each.
 - 4b. Import these hash values into custom hash sets (one or more), add those sets to a custom group, and give the group Ignore status.

- 4c. Process the image with the MD5 and KFF options, and with AD_Alert, AD_Ignore, and the new, custom group selected.
- 4d. During post-processing analysis, filter file lists to eliminate rows representing files with Ignore status.

Hash Set Categories

The highest level of the KFF's logical structure is the categorizing of hash sets by owner and scope. The categories are AccessData, Project Specific, and Shared.

Hash Set Categories

Category	Description
AccessData	The sets shipped with as the Library. Custom groups can be created from these sets, but the sets and their status values are read only.
Project Specific	Sets and groups created by the investigator to be applied only within an individual project.
Shared	Sets and groups created by the investigator for use within multiple projects all stored in the same database, and within the same application schema.

Important: Coordination among other investigators is essential when altering Shared groups in a lab deployment. Each investigator must consider how other investigators will be affected when Shared groups are modified.

What has Changed in Version 6.3 and Later

- See [What Changed in Version 6.3](#) on page 37.
- See [What Changed in FTK and Lab Version 6.4](#) on page 38.
- See [What Changed in March of 2018](#) on page 38.
- See [What Changed in Enterprise Version 6.5](#) on page 39.
- See [What Changed in Version 7.0](#) on page 39.

What Changed in Version 6.3

With the 6.3 release of eDiscovery, Summation, and FTK-based forensics products, the KFF architecture and features have been updated. This architecture is used in versions 6.3 and later.

If you used KFF with applications version 6.2 or earlier, be aware of the following changes in the KFF functionality.

KFF Changes from version 6.2 to 6.3

Item	Description
KFF Server	<p>KFF Server now runs as a different service.</p> <ul style="list-style-type: none">• In versions 5.6 through 6.2, the KFF Server ran as the <i>AccessData Elastic-search Windows Service</i>.• In 6.3 and later, the KFF Server uses the <i>AccessData Cassandra</i> service. <p>Important: If you are upgrading from 6.2 or earlier, all KFF data must be created in or migrated into the new KFF Server.</p> <p>See Migrating Legacy KFF Data from versions 5.6 - 6.2 to 6.4 on page 21.</p>
eDiscovery or Summation KFF Server Configuration Files	<p>In eDiscovery or Summation, there are two configuration files that configure the location of the KFF server.</p> <p>See Configuring the KFF Server Location on Summation or eDiscovery on page 19.</p> <p>The location format and port value in those files have changed.</p> <p>In 5.6 - 6.2, the following was used:</p> <pre><add key="KffElasticSearchUrl" value="http://localhost:9200" /></pre> <p>In 6.3 it was changed to:</p> <pre><add key="KFFServerUrl" value="localhost:9042" /></pre> <p>Note: The "http://" text is no longer used and Cassandra uses port 9042 instead of 9200.</p> <p>There is also a new line:</p> <pre><add key="KFFServerDBType" value="Cassandra" /></pre>

KFF Changes from version 6.2 to 6.3

Item	Description
Hash Manager Migration Tool	<p>If you are upgrading from 5.6 through 6.2, there is a new tool that lets you migrate custom KFF data to the new KFF Server on 6.3.</p> <p>See Migrating Legacy KFF Data from versions 5.6 - 6.2 to 6.4 on page 21.</p> <p>Important: NIST NSRL, NDIC HashKeeper, or DHS library data from 6.2 and earlier will not be migrated when using the Migration Tool. You must re-import those using the 6.3 KFF Import Tool.</p> <p>See About Importing Pre-defined KFF Data Libraries on page 28.</p>
KFF Import Utility	<p>This utility has been updated to use the new KFF Server.</p> <p>If you are upgrading from 5.6 - 6.2, make sure to install and use the new 6.3 version.</p> <p>See Using the KFF Import Utility on page 26.</p>
NIST NSRL	<p>To import NSRL data, you can do either of the following:</p> <ul style="list-style-type: none">• Download version 2.54 files from AccessData and import them.• Download version 2.58 or later RDS files from nist.gov and import them. <p>See Importing the NIST NSRL Library on page 29.</p>
Export/Import	<p>When you export and import KFF data, the Binary format (Entire Library) is no longer available. CSV is the only export format supported.</p>
Geolocation data	<p>Geolocation data is installed independently and is no longer linked to KFF.</p>

What Changed in FTK and Lab Version 6.4

- There is a new verification functionality within the KFF import tool that allows users to verify that all of the hashes in a given import file are contained in the KFF database. The file types supported for verification include: CSV, TSV, .Hash, HDB, HKE, .KFF, VIC, XML, NSRL. (12839)
- The KFF migration utility allows users to migrate edited 6.3 KFF data to an empty 6.4 KFF database. (13029)

Note: Locked/Protected sets will not be migrated from 6.3 to 6.4 in KFF. These will need to be imported.

- Only the Project VIC and NSRL sets are locked/protected. All other sets in the KFF can be modified and archived.
- NDIC or DHS sets cannot be migrated into the 6.4 version of KFF.

See the FTK and LAB 6.4 Release Notes.

What Changed in March of 2018

A new version Cassandra was released for use as the KFF Server: Version 3.11.2

See [About KFF Server Versions](#) on page 12.

See the *KFF Release Notes* from March 2018 for details.

What Changed in Enterprise Version 6.5

No changes were made and you still use the same KFF Server: Version 3.11.2

What Changed in Version 7.0

No changes were made and you still use the same KFF Server: Version 3.11.2

However, AccessData is no longer distributing NDIC Hashkeeper and DHS libraries.